

# DCE 11/13 H

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 232792

## The perfect blend of performance and style

This appliance can be integrated anywhere – not only on account of its compact format, but also in terms of design: its minimalistic look allows it to blend elegantly into any surroundings, with installation above the sink or washbasin. The same goes for matching wall mounted taps, which you can also obtain from us. When it comes to performance levels, our instantaneous water heater has nothing to hide either: its electronic control system reliably ensures accurate temperature settings.



## The main features

Compact instantaneous water heater with electronic closed-loop control

---

Very good energy efficiency thanks to 3i technology

---

Accurate temperature setting in the range of 20-60 °C

---

Adjustable temperature limit as anti-scalding protection for children

---

For oversink installation

---

Exceptionally slimline, compact design



Type	DCE 11/13 H
Part no.	232792

### Technical data

Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ )	900 $\mu\text{S/cm}$
Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	415 V
Rated output	11,2/13,5 kW
Rated output 1	10,1/12,2 kW
Rated output 2	11,2/13,5 kW
Rated output 3	12,1/14,5 kW
Rated current	18,7/19,5 A
Rated current 1	17,8/18,5 A
Rated current 2	18,7/19,5 A
Rated current 3	19,4/20,2 A
Fuse protection	16/20 A
Fuse protection 1	16/20 A
Fuse protection 2	16/20 A
Fuse protection 3	20/20 A
Frequency	50/60 Hz
Frequency 1	50/60 Hz
Frequency 2	50/60 Hz
Frequency 3	50/- Hz

Phases	3/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 380 V)	900 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 400 V)	900 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 415 V)	900 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 380 V)	1100 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 400 V)	1100 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 415 V)	1100 $\Omega$ cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 380 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 400 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$ and 415 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 380 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 400 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^{\circ}\text{C}$ and 415 V)	909 $\mu\text{S}/\text{cm}$
IP rating	IP 24
Temperature setting	20-60 $^{\circ}\text{C}$
Colour	white
ON	>2,5 l/min
Height	293 mm
Width	188 mm
Depth	99 mm
Weight	2.20 kg
Energy efficiency class	A

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.